

United States Patent [19]

Sanchez et al.

[54] METHODS FOR HANDLING MASA

[75] Inventors: Victor R. Sanchez, Fontana; Alberto Ceja, Pico Rivera; Rigoberto Angulano, Baldwin Park, all of Calif.

[73] Assignee: Machine Masters, Inc., Pomona, Calif.

[21] Appl. No.: 476,198

[22] Filed: Jun. 7, 1995

Related U.S. Application Data

[62] Division of Ser. No. 192,458, Feb. 7, 1994.

[51] Int. Cl.⁶ _____ A21C 9/00


[52] U.S. Cl. _____ 426/496; 426/502; 426/503;
426/512; 426/518; 99/443 C; 99/353; 198/604;
198/607; 198/626.1; 221/84

[58] Field of Search _____ 426/391, 496,
426/502, 503, 516-518, 512, 549; 99/443 C,
352, 353; 198/604, 607, 626.1; 221/71,
74, 84

[56] References Cited

U.S. PATENT DOCUMENTS

3,693,533	9/1972	Liepa	_____	99/234
3,853,016	12/1974	Lane, III et al.	_____	74/231
3,869,971	3/1975	Driscoll	_____	99/353
4,304,326	12/1981	Fowler	_____	198/623
4,334,845	6/1982	Tanminen	_____	99/353 X
4,640,843	2/1987	Matuszak et al.	_____	426/560
4,661,364	4/1987	Campbell	_____	426/496
4,778,690	10/1988	Sadel, Jr. et al.	_____	426/560
4,978,548	12/1990	Cope et al.	_____	426/439
4,985,269	1/1991	Irvin et al.	_____	426/560





USC 5235A

[11] Patent Number: 5,635,235

[45] Date of Patent: Jun. 3, 1997

5,050,727 9/1991 Akasaka 198/626.1
5,158,792 10/1992 Modikawa et al. 426/503 X
5,200,203 4/1993 Hayashi 198/604 X
5,272,962 12/1993 Kageyama et al. 99/353

Primary Examiner—Milton Cano

Attorney, Agent, or Firm—Keith A. Newbury, Esq.; Pretty,
Schroeder, Brueggemann & Clark

[57] ABSTRACT

Masa handling methods for the continuous processing of masa type dough in conjunction with commonly available feed processing equipment, such as a masa extruder, an oven, or cooling apparatus. One masa handling method includes a masa separator having a pair of opposed, endless belt conveyors having facing surfaces spaced apart to receive a generally continuous masa stream output from a nozzle on the masa extruder. When the masa stream moves between the conveyors, it is gripped by their facing surfaces and moved away from the nozzle, causing the masa to be separated into individual pieces, or logs. The masa handling method can also include feeding the masa to masa hoppers fed by at least two endless belt conveyors arranged in upstream and downstream positions relative to each other. The masa is transported along the conveyors and is automatically diverted into one masa hopper by a diverter gate operated by a controller that receives a signal from a sensor sensing a masa level within an associated one of the hoppers. The hopper has one or more rotating shafts having projections to remove gas bubbles from the masa and force it toward the sheeter rollers. A pair of primary rollers with scrapers can be provided within the hopper to roll the masa to an intermediate thickness before it passes between the sheeter rollers.

20 Claims, 4 Drawing Sheets

